

## INSTALLATION INSTRUCTIONS

### 1. LAYING INSTRUCTION

Please read these instructions thoroughly before installation.

#### Tools required:

- o Mohair roller;
- o Tape measure;
- o Craft knife;
- o Pencil;
- o Straight edge;
- o Chalk line;
- o Cloth;
- o Rubber hammer.

#### Measurements:

- o Find the center of the room, with a chalk line from the middle of A1, then make a line from the middle of wall B to the middle of wall B1;
- o Check that the intersection of the two lines forms a 90° angle;
- o If laying in diagonal, mark two diagonal lines starting from the intersection point, dividing the 90° angle in half (forming like this a 45° angle).

#### Measurements check:

- o Check the room dimensions by measuring or placing the tiles (without gluing) from the middle;
- o Make sure that the widths of the tiles that will be near the wall are identical and greater than 5cm (2");
- o If necessary repeat the previous step by drawing new parallel lines to the first ones.

#### Laying:

- o Only use CL-Contact adhesive for installation (water based latex contact adhesive);
- o Apply the adhesive by mohair roller;
- o Follow the instructions on the adhesive package;
- o Install the lines from the center along the marked line, preferably using "brick-bond" system.

#### Last row:

- o Cut the tiles near the wall as indicated.

1/1

