

JÕUDLUSKINNITUS

Nr. 64027 -a-CPR_2020.12.1

Tootetüibi ainulaadne identifitseerimiskood	EUROTHANE E WALL
Kavandatud kasutusala(d)	Hoonete termoisolatsioon
Tootja	Recticel NV - Zuidstraat 15 - B-8560 Wevelgem
AVCP süsteem(id)	AVCP 3
Harmoniseeritud standard	EN 13165:2012 + A2:2016
Teavitatud asutus(ed)	Teavitatud testimislabor nr NB 1234, NB 1136, NB 0071 & NB 0751 määrasid kindlaks tootmistüübi süsteemis AVCP 3.

Põhiomadused	Jõudlus (Jõudluse mittedeklarerimist tähistavad tähed NPD (No performance determined), jõudlus tuvastamata)	
Tuletundlikkus	Tuletundlikkus	E
Tuletundlikkus – lõppkasutus	Tuletundlikkus – lõppkasutus	NPD
Soojustakistus	Soojustakistus (RD m ² K/W)	0,90 d _N 20 mm 9,05 d _N 200 mm
	Soojusjuhtivus (λD W/mK)	0,022
Paksus	dN: 20–200 mm	T2
Survetugevus	20 – 49mm: CS(10/Y)100 50 – 200mm: CS(10/Y)150	
Tömbetugevus/nihkumiskäitumine	Tömbetugevus tasapindadega risti: Nihkejoud: Nihketugevus:	20 – 129 mm: TR80 130 – 200 mm: TR60 NPD NPD
Veelabilaskvus	Veeimavus - lühiajaline, osaline sattumine vedelikku - pikaajaline, osaline sattumine vedelikku - pikaajaline, täielikult vedelikuga kaetud Tasapinnalisus pärast ühepoolset niisutamist	NPD NPD WL(T)2 NPD
Veeauru läbilaskvus	Veeauru ülekanne	NPD
Akustiline neeldumisindeks	Helineelduvus	NPD
Otsese õhus edasikanduva heli isolatsiooniindeks	Helineelduvus	NPD
Süttimine pideval hõõgumisel	Harmoniseeritud testimismeetod puudub	
Ohtlike ainete vabanemine siseruumidesse	Harmoniseeritud testimismeetod puudub	
Tuletundlikkuse kestvus soojuse, kulumise, vananemise/lagunemise toimel	Tuletundlikkus ei muutu ajas	
Mõõtmete stabiilsus määratud temperatuuri- ja niiskustingimustel	48 h, 70 °C, 90% suhtelist niiskust 48 h, -20 °C	NPD NPD
Deformatsioon määratletud survekoormusel ja temperatuuritingimustel	40 kPa, 70 °C, 168 h	NPD
Surveroome		NPD

Ülalkirjeldatud toote jõudlus vastab deklareeritud jõudlus(t)ele. Käesolev jõudluskinnitus on väljastatud kooskõlas ELi määrusega nr 305/2011 ning ülalnimetatud tootja ainuvastutusel.

Tootja poolt allkirjastanud:

at Wevelgem on December 1st 2020

Wim Giebens – Industrial Manager Recticel Building Insulation

FEEL
GOOD
INSIDE

RECTICEL
insulation

DECLARATION OF PERFORMANCE

No. 64027 -a-CPR_2020.12.1

Unique identification code of the product-type	EUROTHANE E WALL	
Intended use/es	Thermal insulation for buildings	
Manufacturer	Recticel NV - Zuidstraat 15 - B-8560 Wevelgem	
System/s of AVCP	AVCP 3	
Harmonised standard	EN 13165:2012 + A2:2016	
Notified body/ies	Notified testing laboratory No. NB 1234, NB 1136, NB 0071 & NB 0751 determined the production type under system AVCP3.	

Essential characteristics	Performance	
	(The letters 'NPD' (No Performance Determined) are indicated where no performance is declared.)	
Reaction to fire	Reaction to fire	E
Reaction to fire – end use	Reaction to fire – end use	NPD
Thermal resistance	Thermal resistance (R_D in m^2K/W)	0,90 for d_N 20mm 9,05 for d_N 200mm
	Thermal conductivity (λ_D in W/mK)	0,022
Thickness	d_N : 20-200 mm	T2
Compressive strength	20 – 49mm: CS(10/Y)100 50 – 200mm: CS(10/Y)150	
Tensile strength/shear behaviour	Tensile strength perpendicular to faces:	20 – 129 mm: TR80 130 – 200 mm: TR60
	Shear strength:	NPD
	Shear modulus:	NPD
Water permeability	Water absorption - short term by partial immersion - long term by partial immersion - long term by total immersion Flatness after one-sided wetting	NPD NPD WL(T)2 NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Direct airborne sound insulation index	Sound absorption	NPD
Continuous glowing combustion	No harmonized test method available	
Release of dangerous substances to the indoor environment	No harmonized test method available	
Durability of reaction to fire against heat, weathering, ageing / degradation	Reaction to fire does not change with time	
Dimensional stability under specified temperature and humidity conditions	48h, 70°C, 90% R.H.	NPD
	48h, -20°C	NPD
Deformation under specified compressive load and temperature conditions	40 kPa, 70°C, 168h	NPD
Compressive creep		NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

at Wevelgem on December 1st 2020

Wim Giebens – Industrial Manager Recticel Building Insulation

FEEL
GOOD
INSIDE

RECTICEL
insulation