



DECLARATION OF PERFORMANCE
 DOP n° 120210065B 2019-01-01
FOAMGLAS®READY BOARD T3+



| | |
|---|---|
| 1. Unique identification code of the product-type | FOAMGLAS®READY BOARD T3+ DOP n° 120210065B 2019/01/01-ThIB-CG-EN13167-PL(P)1,5-DS(70,90)-CS(Y)500-BS450-TR150-WS-WL(P)-Mu |
| 2. Identification of the construction product as required under Art. 11(4) | Cellular glass - READY BOARD T3+ |
| 3. Intended use or uses of the construction product | Thermal insulation for buildings |
| 4. Name and contact address of the manufacturer as required pursuant Art. 11(5) | PCE-Pittsburgh Corning Europe NV/SA - Albertkade 1 - B3980 Tessenderlo (B) www.foamglas.com quality-compliance@foamglas.com |
| 5. Name of the authorised representative whose mandate covers the tasks specified in Art. 12(2) | none |
| 6. System or systems AVCP as set out in Annex V | AVCP system 3 |
| 7. Harmonised standard | EN 13167 |
| Notified body | Thermal conductivity - BBRI (No. 1136) & FIW (No. 751) / Fire reaction - WFGRT (No. 1173) / Compressive strength - BBRI (No. 1136) |

8. Table 1

| Essential characteristics | Performance | |
|---|---|--|
| | Thermal resistance | Thermal resistance (RD-value) |
| | Thermal conductivity (λD-value) | λD ≤ 0.036 W/(m•K) |
| | Thickness | from 50 to 200 mm |
| Reaction to fire Euroclass characteristics | Reaction to fire | Euroclass E |
| Durability of thermal resistance against heat, weathering, ageing/degradation | Thermal resistance (RD-value) | RD-value see table 2 |
| | Thermal conductivity (λD-value) | λD ≤ 0.036 W/(m•K) |
| | Durability characteristics | Thermal conductivity of cellular glass products does not change with time, experience has shown the cell structure to be stable. |
| Durability of reaction to fire against heat, weathering, ageing/degradation | Dimensional Stability | DS (70/90) |
| | Durability characteristics | The fire performance of cellular glass does not deteriorate with time. |
| Compressive strength | Compressive strength | CS ≥ 500 kPa |
| | Point load | PL ≤ 1,5 mm |
| Tensile/flexural strength | Bending Strength | BS ≥ 450 kPa |
| | Tensile strength parallel to faces | NPD |
| | Tensile strength perpendicular to faces | TR ≥ 150 kPa |
| Durability of compressive strength against aging degradation | Compressive creep | CC(1,5/1/50)225 |
| Water permeability | Water absorption (short) | WS |
| | Water absorption (long) | WL(P) |
| Water vapour permeability | Water vapour resistance | ∞ infinite |
| Acoustic absorption index | Sound absorption | AP1 → NPD |
| Release of dangerous substances to the indoor environment | Release of dangerous substances | NPD |
| Continuous glowing combustion | Continuous glowing combustion | no glowing combustion |

EN 13167:2012 + A1:2015

Table 2

| Thickness (mm) | Thermal resistance (m²K / W) | Thickness (mm) | Thermal resistance (m²K / W) |
|----------------|------------------------------|----------------|------------------------------|
| 50 | 1,35 | 135 | 3,75 |
| 55 | 1,50 | 140 | 3,85 |
| 60 | 1,65 | 145 | 4,00 |
| 65 | 1,80 | 150 | 4,15 |
| 70 | 1,90 | 155 | 4,30 |
| 75 | 2,05 | 160 | 4,40 |
| 80 | 2,20 | 165 | 4,55 |
| 85 | 2,35 | 170 | 4,70 |
| 90 | 2,50 | 175 | 4,85 |
| 95 | 2,60 | 180 | 5,00 |
| 100 | 2,75 | 185 | 5,10 |
| 105 | 2,90 | 190 | 5,25 |
| 110 | 3,05 | 195 | 5,40 |
| 115 | 3,15 | 200 | 5,55 |
| 120 | 3,30 | | |
| 125 | 3,45 | | |
| 130 | 3,60 | | |

9. The performance of the product is in conformity with the declared performance . This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer

Piet Vitse, European Director Norms & Standards, Product & Systems Certifications, Policy and Advocacy

Tessenderlo (B),01.01.2019

Previous version: 01.01.2018