

SIRIUS

SCHEDA TECNICA PRODOTTO - TECHNICAL DATA SHEET
Gres porcellanato colorato in massa - Fully-coloured porcelain tiles

POLIS
CERAMICHE
DATA - DATE: 9 MARZO 2022
VERS. 02

DATI GENERALI - GENERAL DATA

SERIE-SERIES :	SIRIUS
FORMATI-SIZES :	60X120 - 60X60 - 30X60
NOMI-NAMES :	POLARIS - CASTOR - VEGA - ANTARES
COLORI-COLOURS :	BIANCO - GRIGIO CHIARO - GRIGIO - ANTRACITE WHITE - LIGHT GREY - GREY - DARK GREY
SUPERFICIE-SURFACE :	MAT
NR. COLORI-NR. COLOURS :	4










ACCESSORI - ACCESSORIES

FONDI-TILES :	X	BATTISCOPIA-BULLNOSE:	X
DECORI-DECORS :	X	GRADINO-STEP:	X

USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Esterno - Riv. Interno
Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile

CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)
Appendice G - Classe di appartenenza **B1a** - Class of **B1a**

RESISTENZA AL GELO FROST RESISTANCE		SI	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) HARDNESS (MOHS)		7	UNI EN 101
RESISTENZA ALL'ABRAZIONE RESISTANCE TO DEEP ABRASION		≤ 175 mm³	EN ISO 10545-6
SPESSORE IN BASE AL FORMATO THICKNESS IN REFERENCE TO THE SIZES		9 mm	EN ISO 10545-2
SCIVOLOSITA' SLIPPERINESS		R 10	DIN 51130
		A+B	DIN 51097
		>μ 0,40 Attrito soddisfacente Acceptable Friction	D.M.236-89 Rif. B.C.R.A.
RESISTENZA ALLE MACCHIE RESISTANCE TO STAINING		5	EN ISO 10545-14
RESISTENZA CHIMICA RESISTANCE TO CHEMICALS		A-LA-HA	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE/MODULO DI ROTTURA BENDING STRENGTH/BREAKING STRENGTH		≥ 35 N/mm²	EN ISO 10545-4
ASSORBIMENTO WATER ABSORPTION		≤ 0,5%	EN ISO 10545-3