

STONEHEART

Polis
CERAMICHE
DATA - DATE: 9 MARZO 2022
VERS. 02

SCHEDA TECNICA PRODOTTO - TECHNICAL DATA SHEET

Gres porcellanato colorato in massa - Fully-coloured porcelain tiles

DATI GENERALI - GENERAL DATA

SERIE-SERIES:	STONEHEART
FORMATI-SIZES:	30x60 - 60x60 - 60x120
NOMI-NAMES:	NIGHTSTONE - SILVERSTONE - LANDSTONE - SUNSTONE
COLORI-COLOURS:	GRIGIO - GRIGIO CHIARO - MARRONE - BEIGE GREY - LIGHT GREY - BROWN - BEIGE
SUPERFICIE-SURFACE:	MAT
NR. COLORI-NR. COLOURS:	4

ACCESSORI - ACCESSORIES

FONDI-TILES:	X	BATTISCOPIA-BULLNOSE:	X
DECORI-DECORS:	X	GRADINO-STEP:	X










USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Esterno - Riv. Interno

Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile

CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)

Appendice G - Classe di appartenenza B I a - Class of B I a

RESISTENZA AL GELO FROST RESISTANCE		SI	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) HARDNESS (MOHS)		6	UNI EN 101
RESISTENZA ALL'ABRASIONE RESISTANCE TO DEEP ABRASION		≤ 175 mm ₃	EN ISO 10545-6
SPESSORE IN BASE AL FORMATO THICKNESS IN REFERENCE TO THE SIZES		9 mm	EN ISO 10545-2
SCIVOLOSITA' SLIPPERINESS		R 9	DIN 51130
		>μ 0,40 Attrito soddisfacente Acceptable Friction	D.M.236-89 Rif. B.C.R.A.
RESISTENZA ALLE MACCHIE RESISTANCE TO STAINING		5	EN ISO 10545-14
RESISTENZA CHIMICA RESISTANCE TO CHEMICALS		A-LA-HA	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE/MODULO DI ROTTURA BENDING STRENGTH/BREAKING STRENGTH		≥ 35 N/mm ₂	EN ISO 10545-4
ASSORBIMENTO WATER ABSORPTION		≤ 0,5%	EN ISO 10545-3