

DECLARATION OF PERFORMANCE

- Name and trade name of the construction product:
 Ventilation outlets for bitumen fusible roofs
- 2. Construction product type designation: K40 Ø75 x 275 mm, K41 Ø110 x 355 mm
- 3. Intended use or uses:

WIRPLAST ventilation outlets are intended for draining water vapor that accumulates under waterproofing or thermal insulation of roof coverings and for ventilation of unused attics. They can be used on flat or pitched roofs.

- 4. Name and address of the manufacturer, as well as the place of manufacture of the product: WIRPLAST Więcek Spółka Jawna , ul. Stawowa 9A, 42-287 Babienica. Polska
- 5. Solution 5. Name and legal address of the authorized representative, if authorized:
- 6. The national system of checking and evaluating the stability of operational characteristics: 4
- Country technical assessment: ITB-KOT-2022/2177 1st edition. "Wirplast ventilation outlets and fans" Technical evaluation institution: Institute of Construction Technology, 00-611
- 8. Warsaw, Filtrova street 1
- 9. Declared performance characteristics:

The main characteristics of the construction product for the intended use or types of use	Declared performance characteristics	Notes
Vicat softening temperature, °C	≥ 60	
Charpy impact strength kJ/m ²	≥ 25	
Thermal stability	no cracks, flaking, loose joints or bubbles	
Dimensional and shape stability at (70±2)	≤ 1,0	
°C /3h, dimensional change %	There are no changes in shape or surface defects	
Resistance to accelerated aging after irradiation with 2600MJ/m2	discoloration no greater than 3rd grade gray scale	

9. The operational characteristics of the product indicated above correspond to all the declared operational characteristics referred to in point 8. This national declaration of performance has been issued in accordance with the Law of 16 April 2004 on construction products and is the sole responsibility of the manufacturer.

Babienica, 2022.03.25

On behalf of the manufacturer:











