

# JÕUDLUSKINNITUS

EE

Nr. 64678-a-CPR\_2015.11.1

Tootetüübi ainulaadne identifitseerimiskood	EUROWALL
Kavandatud kasutusala(d)	Hoonete termoisolatsioon
Tootja	Recticel NV - Zuidstraat 15 - B-8560 Wevelgem
AVCP süsteem(id)	AVCP 3
Harmoniseeritud standard	EN 13165:2012 + A2:2016
Teavitatud asutus(ed)	Teavitatud testimislabor nr NB 1136 & NB 0071 määrasid kindlaks tootmistüübi süsteemis AVCP 3.

Põhiomadused	Jõudlus	
	(Jõudluse mittedeclareerimist tähistavad tähed NPD (No performance determined), jõudlus tuvastamata)	
Tuletundlikkus	Tuletundlikkus	F
Tuletundlikkus – lõppkasutus	Tuletundlikkus – lõppkasutus	NPD
Soojustakistus	Soojustakistus ( $R_D$ m <sup>2</sup> K/W)	1,35 d <sub>N</sub> 30 mm 8,15 d <sub>N</sub> 180 mm
	Soojusjuhtivus ( $\lambda_D$ W/mK)	0,022
Paksus	d <sub>N</sub> : 30-180 mm	T2
Survetugevus	CS(10/Y)120	
Tõmbetugevus/nihkumiskäitumine	Tõmbetugevus tasapindadega risti: Nihkejõud: Nihketugevus:	TR80 NPD NPD
Veeläbilaskvus	Veeimavus - lühiajaline, osaline sattumine vedelikku - pikaajaline, osaline sattumine vedelikku - pikaajaline, täielikult vedelikuga kaetud Tasapinnalisus pärast ühepoolset niisutamist	NPD NPD WL(T)2 NPD
Veeauru läbilaskvus	Veeauru ülekanne	NPD
Akustiline neeldumisindeks	Helineelduvus	NPD
Otsese õhus edasikanduva heli isolatsiooniindeks	Helineelduvus	NPD
Süttimine pideval hõõgumisel	Harmoniseeritud testimismeetod puudub	
Ohtlike ainete vabanemine siseruumidesse	Harmoniseeritud testimismeetod puudub	
Tuletundlikkuse kestvus soojuse, kulumise, vananemise/lagunemise toimetel	Tuletundlikkus ei muutu ajas	
Mõõtmete stabiilsus määratud temperatuuri- ja niiskustingimustel	48 h, 70 °C, 90% suhtelist niiskust	DS(70,90)2
	48 h, -20 °C	NPD
Deformatsioon määratletud survekoormusel ja temperatuuritingimustel	40 kPa, 70 °C, 168 h	NPD
Surveroome		NPD

Ülalkirjeldatud toote jõudlus vastab deklareeritud jõudlus(t)ele. Käesolev jõudluskindlus on väljastatud kooskõlas ELi määrusega nr 305/2011 ning ülalnimetatud tootja ainuvastutusel.

Tootja poolt allkirjastanud:

at Wevelgem on November 1<sup>st</sup> 2015

Wim Giebels – Industrial Manager Recticel Building Insulation



FEEL  
GOOD  
INSIDE

RECTICEL  
insulation

# DECLARATION OF PERFORMANCE

## No. 64678-a-CPR\_2015.11.1

Unique identification code of the product-type	EUROWALL
Intended use/es	Thermal insulation for buildings
Manufacturer	Recticel NV - Zuidstraat 15 - B-8560 Wevelgem
System/s of AVCP	AVCP 3
Harmonised standard	EN 13165:2012 + A2:2016
Notified body/ies	Notified testing laboratory No. NB 1136 & NB 0071 determined the production type under system AVCP3.

Essential characteristics	Performance	
	(The letters 'NPD' (No Performance Determined) are indicated where no performance is declared.)	
Reaction to fire	Reaction to fire	F
Reaction to fire – end use	Reaction to fire – end use	NPD
Thermal resistance	Thermal resistance ( $R_D$ in $m^2K/W$ )	1,35 for $d_N$ 30mm 8,15 for $d_N$ 180mm
	Thermal conductivity ( $\lambda_D$ in $W/mK$ )	0,022
Thickness	$d_N$ : 30-180 mm	T2
Compressive strength	CS(10/Y)120	
Tensile strength/shear behaviour	Tensile strength perpendicular to faces:	TR80
	Shear strength:	NPD
	Shear modulus:	NPD
Water permeability	Water absorption	
	- short term by partial immersion	NPD
	- long term by partial immersion	NPD
	- long term by total immersion	WL(T)2
	Flatness after one-sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Direct airborne sound insulation index	Sound absorption	NPD
Continuous glowing combustion	No harmonized test method available	
Release of dangerous substances to the indoor environment	No harmonized test method available	
Durability of reaction to fire against heat, weathering, ageing / degradation	Reaction to fire does not change with time	
Dimensional stability under specified temperature and humidity conditions	48h, 70°C, 90% R.H.	DS(70,90)2
	48h, -20°C	NPD
Deformation under specified compressive load and temperature conditions	40 kPa, 70°C, 168h	NPD
Compressive creep		NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/211, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

at Wevelgem on November 1<sup>st</sup> 2015

Wim Giebens – Industrial Manager Recticel Building Insulation

Wim Giebens – Industrial Manager Recticel Building Insulation

