# PRODUCT DATA SHEET

www.btm.co
Bituminous Waterproofing Membranes Co.
Kemalpasa Org. San. Bölgesi Mah. Gazi Bulvarı. No:
152 Kemalpaşa / İZMİR /TURKEY
Tel:+90 0232 877 04 02 (8 line)
Fax: +90 0232 877 04 10

## BTS-100
## BİTUSOL

Document number :PDS-004-0
Publication Date :05th,Jan.2009 Revision date : -

| | |
|---|---|
| **PRODUCT DESCRIPTION** | Solvent based-cold applied bituminous waterproofing liquid |
| **USAGE** | Besides serving as primer at the waterproofing applications, are used to prevent humidity at the basement walls underground , to produce bituminous protective mortar. Type -1 |
| **APPLICATION METHOD** | Applied with brush. Please refer to application booklet. |
| **STORAGE** | Pails stored away from direct sunlight |
| **ECOLOGICAL DATA** | Can be used in natural atmosphere |

| TEST | METHOD | UNIT | TOLERANCE | VALUES |
|---|---|---|---|---|
| Viscosity at 25$^0$C | TS 103 | cP | - | 25 - 150 |
| Water Content | TS 103 | % | - | 0 |
| Distillation at 0-225 $^0$C | TS 103 | % | Min. | 35 |
| Distillation at 225-360 $^0$C | TS 103 | % | Max. | 65 |
| Residue Penetration at 25$^0$C (100 gr, 5s) | TS 103 | dmm | ±15 | 35 |
| Matter soluble in trichloroethylene | TS 103 | % | Min. | 99 |
| Density | TS 103 | gr/cm$^3$ | ±0,03 | 0,095 |

NPD = (No performance defined)

* For information and advice on the safe handling,storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet

The maufacturer serves the right to modify, at any time, the characteristics of its products