

DECLARATION OF QUALITY No. PY/2013/01

according to Regulation of the European Parliament and of the Council (EU) No. 305/2011
from the 9 of March 2011,
laying down harmonized conditions for the marketing of construction products on the market.

1. *Unique identification code of the product:*
12.135305, 12.135306, 12.170305, 12.170306

2. *Type, batch or serial number or other element allowing identification of the construction product:*

fatrapar 150 / fatrapar 200

foil type A from low density polyethylene (LDPE) produced in thicknesses 0,15 mm a 0,20 mm

3. *The intended use of a construction product in accordance with the relevant harmonized technical specification:*

vapor barrier in the construction industry. More information about the use and installation method are listed in the technical sheet

4. *Name, company, or registered trade mark and contact address of producer:*
PYTLÍK, a.s., IČ: 26459990, Bečovská 1326/9, 104 00 Praha 10 - Uhřetěves, Czech Republic

6. *The system or systems of assessment and verification of constancy of qualities of construction product:*
System 4

7. *The case of the declaration of qualities of a construction product covered by a harmonized standard:*


Initial tests were performed by testing laboratory INSTITUT PRO TESTOVÁNÍ A CERTIFIKACI, a. s., třída Tomáše Bati 299, Louky, 763 02 Zlín, Czech Republic, Notified subject no. 1023
Producer performs production control system.

9. *Qualities listed in declaration:*
see Annex no.1

10. *Product qualities, specified in point no. 1 and no. 2, are in conformity with the qualities in point no. 9.*

*This declaration of qualities is issued under the sole responsibility
producer referred to in point no. 4. Producer signed for and on behalf of:*

In Prague 1.11.2020


Bečovská 1326/9
104 00 Praha 10 - Uhřetěves
+420 222 267 965 +420 777 310 691
www.pytlík.cz
PYTLÍK, a.s. IČ: 26459990

Martin Kádlec
Chairman of the Board of Management
PYTLÍK, a.s.


Sídlo a provozovna Praha : Bečovská 1326/9, Praha 10 Uhřetěves, 104 00
Provozovna Brno : Řípská 1153/20a, 627 00 Brno

ver.201101en

Annex No. 1: Qualities listed in declaration



DEKSEPAR (thickness):			0,15 mm	0,20 mm
Basic characteristics	Testing method	Unit	Quality	
Reaction to fire	EN 13501-1 +A1	class	F	F
Waterproof (when water pressure 2 kPa)	EN 1928 method A	-	conform	conform
Tensile qualities - highest tensile strength - In the longitudinal direction - In the transverse direction	EN 12311-2	N/50 mm	100 55	140 110
Tensile qualities - ductility - In the longitudinal direction - In the transverse direction	EN 12311-2	%	250 330	700 700
Resistance to tearing (nail shank) - In the longitudinal direction - In the transverse direction	EN 12310-1	N	60 60	85 75
Resistance to impact	EN 12691	mm	NPD	NPD
Resistance of joint	EN 12317-2	N/50 mm	NPD	NPD
Water vapor permeability - Diffusion resistance factor μ - Equivalent diffusion thickness s_d	EN 1931	- m	550 000 (\pm 50 000) 82,5 (\pm 7,5)	550 000 (\pm 50 000) 110 (\pm 7,5)
Durability - water vapor permeability after artificial aging	EN 1296 a EN 1931	-	conform	conform
Durability - Resistance to alkalis	EN 1847 a EN 12311-2	-	NPD	NPD
Hazardous substances	REACH (1907/2006)	-	no contains	no contains
Harmonized technical specification: EN 13984:2013				


 Bečovská 1326/9
 104 00 Praha 10 Uhřetíněves
 +420 222 287 991 +420 777 310 691
 www.pytlík.cz
 PYTLÍK, s.r.o. IČO: 26459990 DIČ: CZ26459990

Sídlo a provozovna Praha : Bečovská 1326/9, Praha 10 Uhřetíněves, 104 00
Provozovna Brno : Řipská 1153/20a, 627 00 Brno

PYTLÍK, a.s.

ver.201101en